

CC2 Series

Compact Two-stage Cylinder Pressure Regulator



The CC2 Series compact two-stage precision pressure regulator is well suited for instrumentation applications requiring a precise and stable delivery pressure. This regulator was originally designed to meet the needs of the instrumentation industry; however, it would also be very useful in many other applications that require a compact two-stage pressure regulator to supply a precise delivery pressure with fluctuating supply pressures.

Another benefit of using the CC2 Series is that internally, it shares some of its design features and options with the time proven CPR-1 Series pressure regulator. These features and options allow the customer to essentially tailor this regulator to accommodate virtually any application requiring low to moderate flow rates. The unit will also be offered with inlet/outlet pressure gauges, CGA connections and relief valves.

The CC2 Series regulator is manufactured in 316L stainless steel as a standard option. Please consult GO Regulator for any optional materials of construction that might be required for toxic or corrosive process gas applications.

Features & Specifications

- Compact size
- Two-stage regulation
- Stainless steel diaphragm
- Gas or liquid service
- Low internal volumes
- Maximum inlet pressure up to 3600 psig
- Outlet pressure ranges: 0–10 psig, 0–25 psig, 0–50 psig, 0–100 psig, 0–250 psig and 0–500 psig
- Cv flow coefficients: 0.06, 0.025, 0.2
- Leak rate, bubble-tight
- Operating temperatures: –40° F to +175° F (–40° C to +80° C)
- Inlet/outlet connections: 1/8" FNPT

pressure regulators

CC2 Series

To Order, contact your local Distributor Link below:
www.goreg.com/distributor/index.htm

Verify that your chosen part number is valid using the GO Wizards at
www.goreg.com/products/matrix/index.htm

How to Order

Standard items in bold

CC – **3** **F** **0** **C** **1** **1** **1** **1** **CGA Fitting** **0** **0** **0** **1** **A** **3** **A** **3** **A**

BODY MATERIAL

- 1 316L stainless steel
- 2 Brass
- 3 Aluminum

PORT CONFIGURATIONS

F Standard
For more port configurations, see page 19.

PROCESS PORT TYPES (GAUGE PORT TYPE, IF NECESSARY)

0 1/8" FNPT (1/8" FNPT gauge ports)

OUTPUT RANGE

- C** 0–10 psig
- D** 0–25 psig
- E** 0–50 psig
- G** 0–100 psig
- I** 0–250 psig
- J** 0–500 psig

DIAPHRAGM TYPE, 1ST STAGE

1 Standard

DIAPHRAGM TYPE, 2ND STAGE

1 Standard

CAP ASSEMBLY, 1ST STAGE

- 1 Tamper-proof, aluminum**
- 4 Tamper-proof, panel mount, aluminum**
- 5 Tamper-proof, captured vent, aluminum**

OPTIONS

- A** EB33 (oxygen cleaning)
- B** EB5 cleaning
- D** Helium leak test
- E** Pressure test certificate
- F** Certificate of Conformity
- G** CMTR

2ND STAGE Cv FLOW

- 3 0.06**
- 5 0.2**
- C 0.025**

2ND STAGE SEAT MATERIAL

- A Tefzel®**
- B CF PTFE**
- H PCTFE (Formerly Kel-F81)**
- Q PEEK™**

1ST STAGE Cv FLOW

- 3 0.06**
- 5 0.2**
- C 0.025**

1ST STAGE SEAT MATERIAL

- A Tefzel®**
- B CF PTFE**
- H PCTFE (Formerly Kel-F81)**
- Q PEEK™**

GAUGES

- 1 Include gauges**
- 2 Omit gauges**
- 3 Customer-supplied**

CGA FITTING

Use '000' to omit CGA
Use 'CUS' for customer-supplied CGA

Maximum Temperature & Operating Inlet Pressures

SEAT MATERIAL	MAXIMUM TEMPERATURE		MAXIMUM OPERATING INLET PRESSURE
Tefzel®	150° F (66° C)	@	3600 psig (24.82 MPa)
CF PTFE	175° F (80° C)	@	3600 psig (24.82 MPa)
PEEK™	175° F (80° C)	@	3600 psig (24.82 MPa)
PCTFE (formerly Kel-F® 81)	175° F (80° C)	@	3600 psig (24.82 MPa)

NOTE: Contact the factory for any additional requirements.

Tefzel® is a registered trademark of the DuPont Company.
Kel-F® is a registered trademark of 3M Company.
PEEK™ is a trademark of Victrex PLC.

Outline & Mounting Dimensions

Weight = 2.1 lbs (0.95 kg)

