


Product Data Sheet

G12AF Type 2 Valve Manifold



The 'G12AF' Type 2 valve manifold is designed for remote mounting to static pressure transmitters. The angled heads allow for panel mounting. The separate vent valve gives full control of venting of the instrument, plus the ability to calibrate in-situ. Each needle valve head is designed for safe and reliable isolation, giving bubble tight shut off, with nonrotating & anti-galling tip and dynamic self-adjusting spindle seal to give long service life in a variety of service conditions.

| Part No. | Connections Size | Α | В | С | D | Weight (Kgs) |
|----------|---------------------|-----|-----|-----|-----|-----------------|
| G12AF | ½" F x F | 2.5 | 1.1 | 4.6 | 3.6 | 1.0 |

Key Features of the Oliver Needle Valve range

- Non rotating tip self centering & anti-galling
- Piston ring gives dynamic adjustment of gland seal in response to pressure change
- Anti-blow out spindle a major safety feature
- Secure seal precision machined to give leak free operation for the life of the valve. Available in either PTFE or graphite foil

Standard Specification

| | Pressure: 6000psi | Packing: PTFE | Handle: T-Bar | Bore: 0.21" (5.4mm) | |
|---|--------------------------------|------------------|---------------------------------|---------------------|--|
| | Temp: 240 deg C | Thread form: NPT | Seat: Metal to metal | CV: 0.46 | |
| ĺ | 2 x 9/32" diameter mounting ho | les included | 1/2" Inlet / Outlet Connections | | |
| ĺ | 1/4" NPT Vent Connection | | | | |

Ordering Code

BT (Typical example) → G12AF S AT G12AF - Female x Female

Material

Type

S - 316S31 Stainless Steel M - Monel (400)

HC - Hastalloy (C276) (Others available)

Optional Connections (NPT Standard)

BT - BSP Taper

BP - BSP Parallel (top sealing)

BTV - BSP Taper Vent

BPV - BSP Parallel Vent

Options

AG - Graphite Foil AT - Anti-Tamper

BKTC - Carbon steel mounting bracket BKTS - Stainless steel mounting bracket

HL - Handle Locking

HL-PI - Handle Locking + Position Indicator

HW - Hand Wheel

LT100 - Cryogenic Head Unit (-100°C)

MT - Metering Tip

NA - NACE MR-01-75 (latest revision)

OXY - Oxygen Cleaned PK - PEEK Soft Tip

PP - Blank Plug In Vent Connection

Rev 1.2