


### **Product Data Sheet**

## **G12FF Type 2 Valve Manifold**



The 'G12FF' Type 2 valve manifold is designed for remote mounting to static pressure transmitters. The separate vent valve gives full control of venting of the instrument, plus the ability to calibrate in-situ. Each needle valve head is designed for safe and reliable isolation, giving bubble tight shut off, with non-rotating & anti-galling tip and dynamic self-adjusting spindle seal to give long service life in a variety of service conditions.

| Part No. | Connections<br>Size | Α   | В   | C   | Weight<br>(Kgs) |
|----------|---------------------|-----|-----|-----|-----------------|
| G12FF    | ½" F x F            | 2.5 | 1.1 | 7.1 | 0.9             |

## **Key Features of the Oliver Needle Valve range**

- Non rotating tip self centering & anti-galling
- Piston ring gives dynamic adjustment of gland seal in response to pressure change
- Anti-blow out spindle a major safety feature
- Secure seal precision machined to give leak free operation for the life of the valve. Available in either PTFE or Grafoil

## **Standard Specification**

| Pressure: 6000psi               | Packing: PTFE    | Handle: T-Bar            | Bore: 0.21" (5.4mm) |
|---------------------------------|------------------|--------------------------|---------------------|
| Temp: 240 deg C                 | Thread form: NPT | Seat: Metal to metal     | CV: 0.46            |
| 1/2" Inlet / Outlet Connections |                  | 1/4" NPT Vent Connection |                     |

# **Ordering Code**

(Typical example) → G12FF

S

ВТ

AT

Type

G12FF - Female x Female

#### Material

S - 316S31 Stainless Steel M - Monel (400) HC - Hastalloy (C276) (Others available)

### **Optional Connections (NPT Standard)**

BT - BSP Taper

BP - BSP Parallel (top sealing) BTV - BSP Taper Vent

BPV - BSP Parallel Vent

### **Options**

AG - Grafoil

AT - Anti-Tamper

BKTC - Carbon steel mounting bracket BKTS - Stainless steel mounting bracket

HL - Handle Locking

HL-PI - Handle Locking + Position Indicator

HW - Hand Wheel

LT100 - Cryogenic Head Unit (-100°C)

MT - Metering Tip

MTG - Tapped Mounting Holes x 2 NA - NACE MR-01-75 (latest revision)

OXY - Oxygen Cleaned PK - PEEK Soft Tip

PP - Blank Plug In Vent Connection 2H - Straight through mounting holes x 2

Rev 1.1